Customer Fork Tool | **ITA Standard** Forks

Phone: _____ Fax: _____

Dealer Name:

(BH)

(H1)

(H2)

(B)

Contact Name:_____ Email:_____

(BH) Back Height Measure from the top to

(H2) Height 2 Measure from the bottom of the top clip to the top of the bottom clip.

(B) Carriage Measure inside the clips on the backside of the forks as indicated by the arrows.

(T) Thickness

(L) Length

Taper (Choose one) -

Standard Full Taper Blunt/No Taper

(H1) Height 1 Measure from the bottom of the


the bottom of the back of the fork.

fork to the bottom of the top clip.

\checkmark	ITA Class	Carriage (B)	Capacity	(BH)	(H1)	(H2)
	II	16"	2,000-5,500 lb	21.5"	18.5"	15.04"
	III	20"	5,501-11,000 lb	26"	22.36"	18.78"
	IV	25"	11,000-17,500 lb	33"	29.25"	23.54"
	Class III - IT	24"	5,501-11,000 lb	31"	28"	22.75"

Measure:

Finish (Choose one) —
Standard Polished



- Tip (Choose one) -	1
Standard 1⁄2"	
FTP Tip 1/8"	
Chisel Tip 1⁄16"	

Machine Model					
Machin	e Capacity				
	inche	es			
(BH) Ba	ack Height				
(H1) He	ight 1				
(H2) He	(H2) Height 2				
(B) Carı	(B) Carriage				
(L) Length					
(T) Thicknes					
(W) Width					
Shape	Standard Rounde	ed			
	Squared Block				
Class					
	IV III Clips-IT				
Тір	Standard FTP Tip				
	Chisel Tip				
Taper	Standard Full Tap	ber			
	Blunt/No Taper				
Finish	Standard Dolishe	d			



he sole property of Arrow Material Handling. Any reproduction in part or as a whole without the written permission of Arrow Material Handling is prohibited.				
Title	ITA Spacing Forks			
DWG.No) .			

Title	ITA Spacing Forks	
DWG.No.		
Drawn By		Date
REV		Sheet

*All Measurements should be provided in inches.